

# Numerical simulation of ductile fracture problems using a weak discontinuity approach

Alfredo E. Huespe

Cimec, Intec, Conicet-UNL, Guemes 3450, 3000 Santa Fe, Argentina

ahuespe@intec.unl.edu.ar

A finite thickness band method, for computational simulation of ductile fracture problems, is presented. The methodology is based on a Gurson constitutive material model, with material degradation defined through an evolution law of internal variables simulating the process of nucleation, growth and cavitation of micro-voids ([1] and [2]).

In order to provide a regularization of the constitutive model, and therefore, to introduce an objective response for the strain localization process in the material softening regime, a finite thickness band methodology is defined, across which a weak discontinuity is developed. In this context, the thickness “ $D$ ” of the band becomes a material parameter of the model which must be characterized, and governs the energy dissipated during the fracture process ([3]).

The weak discontinuity mode is introduced in the analysis once a material failure criterion, based on the material stability or bifurcation condition, is verified. This criterion also provides additional information about the crack propagation (or weak discontinuity mode) direction.

Several topics, related with the numerical implementation of the model, are additionally addressed in the presentation, such as:

- An embedded finite element technique;
- Different alternatives for determining the fracture path across the finite element mesh: global tracking algorithm and new trends to avoid it;
- Robust numerical schemes (Impl-Ex) to perform the time integration of the model equations.

To show the numerical performance of the algorithm, a number of numerical solutions are presented. Typical bar tests (taken from[4]) are reproduced.

## Bibliography

- [1] Gurson, A., 1975. Plastic Flow and Fracture Behavior of Ductile Materials Incorporating Void Nucleation, Growth and Interaction. Ph.D. thesis, Brown University.
- [2] Tvergaard, V., 1990. Material failure by void growth to coalescence. Adv. Appl. Mech. 27, 83–151.
- [3] A.E. Huespe, A. Needleman, J. Oliver, P.J. Sánchez, A finite thickness band method for ductile fracture analysis, Int. J. of Plasticity, 25 (2009) 2349–2365
- [4] Besson, J., Steglich, D., Brocks, W., 2001. Modeling of crack growth in round bar and plane strain specimens. Int. J. Solids Struct. 38, 8258–8284.